

In the Claims:

Please amend Claims 1, 4, 7, 9, 11, 13, and 16 as follows (the changes in these Claims are shown with ~~strike through~~ for deleted matter and underlines for added matter). A complete listing of the claims proper claim identifiers is set forth below.

1. (Currently Amended) An automatic flushing actuator system for a toilet having a tank and a bowl comprising:

a sensor for detecting the presence of an occurrence said sensor including a transmitter for sending a signal indicating the occurrence;

a receiver for receiving the signal; said receiver being disposed in a housing having a base and a cover, said cover having a horizontally rotatable lever mounted thereon;

a motor and gear mechanism connected to said receiver, said gear mechanism having a cam for engaging an actuator rod which is in contact with said lever; and

a clamp for mounting the housing on a component in the toilet tank.

2. (Original) The automatic flushing actuator of claim 1, wherein said clamp is removably mounted to said housing.

3. (Original) The automatic flushing actuator of claim 1, wherein said clamp is permanently mounted to said housing to prevent theft of the housing.

4. (Currently Amended) The automatic flushing actuator of claim 1, wherein said clamp can be changed from a removable ~~removably mounted~~ configuration on said housing to a ~~permanently mounted~~ locked configuration by rotating the clamp 180 degrees.

5. (Original) The automatic flushing actuator of claim 1 further comprising an insert configured for placement inside said clamp.

6. (Original) The automatic flushing actuator of claim 1, wherein said component is an overflow pipe and said clamp is affixed to said overflow pipe.

7. (Currently Amended) The automatic flushing actuator of claim 6, wherein said housing is affixed to said clamp after said ~~elap~~ clamp is affixed to said overflow pipe.

8. (Original) The automatic flushing actuator of claim 1 further comprising a turret on an upper portion of said cover.

9. (Currently Amended) The automatic flushing actuator of claim 8 further comprising a lever assembly coupling said horizontally rotatable lever to said turret. ~~having an inner surface for mounting said lever on said turret.~~

10. (Original) The automatic flushing actuator of claim 9 further comprising serrations on said turret.

11. (Currently Amended) The automatic flushing actuator of claim 10 further comprising serrations on said inner surface of said lever assembly, wherein said turret serrations engage said lever assembly serrations when said horizontally rotatable lever is rotated thereby locking said lever assembly in a desired position.

12. (Original) The automatic flushing actuator of claim 1 wherein said receiver is wirelessly coupled to said sensor.

13. (Currently Amended) An actuator for an automatic flushing system for use with a toilet having a tank and a bowl comprising:

a housing comprising a base and a cover, said cover having an upper surface; and

a horizontally rotatable lever ~~rotatably~~ mounted on said cover upper surface.

14. (Original) The actuator of claim 13 further comprising guide rails coupled to a slidably receivable clamp of said housing.

15. (Original) The actuator of claim 14, wherein said slidably receivable clamp is removably mounted to said housing.

16. (Currently Amended) The actuator of claim 14, wherein said slidably receivable clamp can be changed from a ~~removably mounted~~ removable configuration on said housing to a ~~permanently mounted~~ locked configuration by rotating said slidably receivable clamp about 180 degrees.

17-23. (Canceled)